

## Model:RT-1649

► COBRASHEILD Windshield Protection Film



| PRODUCT PROPERTIES          | TEST VALUE                |
|-----------------------------|---------------------------|
| Anti-yellowing              | B value<3                 |
| Size                        | 1.52 x 15m                |
| TPU thickness               | 150µm                     |
| Coating thickness           | 15µm                      |
| Adhesive thickness          | 23µm                      |
| Overall thickness           | 188µm/6.5mil ±3%          |
| Coating layer Elongation    | >200%                     |
| Finished flm Elongation     | >300%                     |
| Tensile resistance          | 18Мра                     |
| Tear resistance             | 70N                       |
| Puncture resistance         | 13N                       |
| Base Film Type              | Aliphatic TPU by Argotec  |
| Initial adhesiveness        | >800g                     |
| Hold adhesiveness           | >1300g                    |
| Gloss                       | 95GU                      |
| Scratch repairable          | Self Healing, Hydrophobic |
| Coating adhesion            | Level 5                   |
| Water drop angle            | 85°                       |
| Glue                        | Ashland USA               |
| High-temperature resistance | No change                 |
| Hydrolysis resistance       | No change                 |
| Acid & alkali resistance    | No change                 |
| Oil resistance              | No change                 |
| Warranty                    | 2 years                   |
| <u></u>                     |                           |